



## SPOT POWER 230 Art. 610SG



Art. 610SG - Spot Power 230 Evolution,  
A innesto automatico con comando remoto, monofase 230 Volt

Art. 610SG - Spot Power 230 Evolution,  
Digital Spotter automatic with remote control, single Phase 230 Volt.


### Caratteristiche tecniche | Technical specifications

Potenza nominale al 50%	Rated power at 50%	KVA	Sn 4
Corrente sec. di corto circuito	Sec. short circuit current	KA	3500
Corrente sec. max di saldatura	Sec. max welding current	KA	2800
Tensione secondaria	Secondary voltage	V	7,5
Alimentazione Mod. 230	Single-phase power voltage	V	230
Frequenza nominale	Nominal frequency	HZ	50/60
Fusibili ritardati	Delayed fuses	A	16
Livello temp. trasformatore	Temperature level of power transformer		F
Cl. isolamento trasformatore	Power transformer insulation class		F
Termostato di sicurezza su connettori	Safety thermostat on cable connectors	°C	70
Lunghezza cavo torcia	Length and cross section of torch cable	mm/mm <sup>2</sup>	2500/50
Lunghezza cavo massa	Length and cross section of earth lead	mm/mm <sup>2</sup>	2000/50
Dimensioni Spot Power 230 e 400	Spot Power 230 e 400 dimensions	mm	240x465x295
Peso	Weight	Kg	24

### Dotazioni | Equipment

- Torcia attacco universale
- Martello a battente con elettrodo puntatura e calde
- Telecomando con cavo
- 2 cavi
- 1 massa rapida
- Torch universal connector
- Gun with slide hammer with electrodes (1 x spotting, 1 x shrinking)
- Remote control with cable
- 2 cables
- 1 quick earth electrode

### Dimensioni | Dimension





## SPOT POWER 400 Art. 630SG



Art. 630SG - Spot Power 400 Evolution,  
A innesto automatico con comando remoto, trifase 400 Volt

Item 630SG - Spot Power 400 Evolution,  
Digital Spotter automatic with remote control, 3-phase 400 Volt

### Caratteristiche tecniche | Technical specifications

Potenza nominale al 50%	Rated power at 50%	KVA	Sn 4
Corrente sec. di corto circuito	Sec. short circuit current	KA	3500
Corrente sec. max di saldatura	Sec. max welding current	KA	2800
Tensione secondaria	Secondary voltage	V	7,5
Alimentazione Mod. 400	Three-phase power voltage	V	400
Frequenza nominale	Nominal frequency	HZ	50/60
Fusibili ritardati	Delayed fuses	A	16
Livello temp. trasformatore	Temperature level of power transformer		F
Cl. isolamento trasformatore	Power transformer insulation class		F
Termostato di sicurezza su connettori	Safety thermostat on cable connectors	°C	70
Lunghezza cavo torcia	Length and cross section of torch cable	mm/mmq	2500/50
Lunghezza cavo massa	Length and cross section of earth lead	mm/mmq	2000/50
Dimensioni Spot Power 230 e 400	Spot Power 230 e 400 dimensions	mm	240x465x295
Peso	Weight	Kg	24

### Dotazioni | Equipment

- Torcia attacco universale
- Martello a battente con elettrodo puntatura e calde
- Telecomando con cavo
- 2 cavi
- 1 massa rapida
- Torch universal connector
- Gun with slide hammer with electrodes (1 spoting, 1 x shrinking)
- Remote control with cable
- 2 cables
- 1 quick earth electrode

### Dimensioni | Dimension

